

PRODUCT DATA SHEET

Star Line Single-Section Cabinet

**Standard**

- Complies with ANSI/EIA RS-310-D, IEC 297-1, 19" Mounting, IEC297-2
- Overall cabinet dimensions, EN 61587-1:2012
- Mechanical Structures for Electronic Equipment, DIN41491; PART1, DIN41494; PART7, GB/3047.2-92, UL certified

**Material**

- SPCC Cold-Rolled Steel
- Thickness: 2mm for 19" rails: others parts: 1.0mm

**Color**

- RAL7035
- RAL9004

**Loading Capacity**

- Static load: Up to 90KG (198 lbs)



**Feature**

- Single -section wallmount cabinet.
- Tempered glass front door with 180° swing and rotary key lock.
- Removable side panels with locks.
- Adjustable front and rear mounting posts with # 12-24 threaded holes for cage nuts.
- Cable entry panel with brush on the top cover and perforations on the bottom plate.
- Supplied with 1 UL installed fan.
- Additional fan available upon request.
- Available in heights from 6u to 23u, depths 450 or 600mm. Flat packing 9easy assembly) for space-saving.
- Fully assembled option available for quick installation.

**Definition of Code**

NTFWCXXUXXX (450 or 600U)

└─ Cabinet capacity( U) : 6, 9, 12, 16, 20

**Main Part**

S/N	Specification	Qty	Material	Surface Finish	Remark
1	Frame	1	SPCC t1.0	Powder coated	----
2	Side panel	2	SPCC t1.0	Powder coated	----
3	Front door	1	5MM toughed glass	----	----
4	19 " rails	4	SPCC t1.2	Powder coated	----
A	M6 screw& nuts	10	Steel	Color zinc	----
B	Trox tooling	1	Steel	Black	----

**Specification**

Model No.	Size (U)	Width (mm)	Depth(D)(mm)	Color	Max Weight
NTFWC6U450	6	560	450	Black	50kg (110lb)
NTFWC9U450	9	560	450	Black	60kg (132lb)
NTFWC12U450	12	560	450	Black	70kg (154lb)
NTFWC6U600	6	560	600	Black	50kg (110lb)
NTFWC9U600	9	560	600	Black	60kg (132lb)
NTFWC12U600	12	560	600	Black	70kg (154lb)
NTFWC16U600	16	560	600	Black	80kg (176lb)
NTFWC20U600	20	560	600	Black	90kg (198lb)

**Details**

