

PRODUCT DATA SHEET

EngineerPro® CAT6 Unshielded Patch Panels

Overview

Nitrotel EngineerPro® Cat6 Patch Panels offer exceptional interconnection in 10/100/1000 Base-T Gigabit Ethernet applications. Metal frame is made of heavy-duty gauge steel and formed to create a robust surface capable of withstanding the forces generated while punching down cables to the panel. EngineerPro® Cat6 unshielded patch panel has 12, 24 or 48 Cat 6 RJ45 ports on the front and corresponding 110 style IDC punchdown connectors on the rear.

Key Features

- Include silk-screened port numbers and paper label holders.
- Include color code labels for T568A and B wiring schemes.
- · Utilizes industry standard termination 110 style termination punchdown.
- Mounts to the front or rear of any standard EIA 19" spaced rack. 12-port suitable for wall mount with 89D bracket.

Technical Specifications

Performance:	Specifications:	
Cat6	250 MHz +	
Compliance	Meets ANSI/TIA-568.2-D transmission performance	
	specifications and ISO 11801 Class E channel and	
	component requirements at swept frequencies up	
	to 250 MHz.	
IDC Block:	Specifications:	
Туре	110 Punchdown	
Contact Construction	Phosphor bronze with tin plated	
Operating Life	200 re-terminations (min.)	
Cabling	22-26 AWG, Stranded and Solid UTP cable	
Electrical:	Specifications:	
Wiring for	T568A or T568B	
Dielectric Withstand	1000 VAC RMS @ 60Hz	
Voltage/current	150 VDC @ 1.5A, max., > 100mW @ 500 Vdc	
RJ45 Connector:	Specifications:	
Contact Construction	Phosphor bronze, 50μ in. gold plating	
Insertion Life	750 insertions, min., @ < 0.2 dB of insertion loss	
Insertion Force	900 gms for 8 contacts	
Retention Strength	7,7 Kgs between Jack and Plug	
Housing	High-impact thermoplastic, UL94V-0 rated	



EngineerPro® Unshielded Network Component

EngineerPro® Category 6 Punchdown Patch Panels:

NTPP6E12U 12-Port 24-Port, 1 RU NTPP6F24U 48-Port, 2 RU NTPP6E48U

EngineerPro® Category 6 Patch Cords NTPC6EXX*YY** Foot Lengths:

EngineerPro® Category 6 UTP Cable



BU	RD
GY	ВК
WH	YL
GN	PR

Item	Outer Jacket	Overall diameter(mm)
Р	CMP	6.4±0.2
С	CM	6.4±0.2
R	CMR	6.4±0.2
L	LSZH	6.4±0.2
Е	LDPE	6.4±0.2

Available Cable Management:

Horizontal Cable Managers Blank Filler Panels **Brush Panels** Hook & Loop Fasteners

* For standard lengths (01, 03, 05, 07, 10, 15 or 20 Ft) change the XX in

part number to the desired length.
** For standard cable colors add suffix BU (Blue), WH (White), BK (Black), GR (Green), RD (Red), GY (Gray) or YL (Yellow) after desired lendth at the end of the part number. For example, the part number for a blue 3 foot patch cord is NTPC6E03BU.



EngineerPro® Cat 6 **UTP** Cable



EngineerPro® Cat 6 **UTP Patch Cord**

























NTPP6E12U








NTPP6E24U





NTPP6E48U

