Nitrotel Manufacturing
Low Voltage Products & Fiber Optic

Part No.
NTSOHOXXU500

PRODUCT DATA SHEET

SOHO Cabinet

Standard
- Complies with ANSI/EIA RS-310-D, IEC 297-1, 19" Mounting, IEC297-2 Overall cabinet dimensions, EN 61587-1:2012 mechanical Structures for Electronic Equipment, DIN41491; PART1, DIN41494; PART7, GB/3047.2-92 standards, UL certified

Material
- SPCC Cold Rolled Steel;
- Thickness: 19" rails: 1.2mm, others: 1.0mm

Color
- RAL7035
- RAL9004

Loading Capacity
- Static loading: Up to 60 KG

Feature
- Disassembled and small packaging, easy to deliver and carry.
- Special design front and back frames are with good stability.
- 16 screws are needed to assemble the whole enclosure. It will take only 3 minutes to assemble the enclosure by one person.
- Wide glass front door allows and excellent view of the interior of the cabinet. Opening direction could be changed easily.
- Cable entries are available on top, bottom and back of enclosure, suitable for different places.
- Maximum Loading capacity: 60kgs.

Definition of Code

NTSOHO ■■ U500

■■ — Cabinet capacity(U): 6, 9, 12

786.409.3741 sales@nitrotelmanufacturing.com WEB www.nitrotelmanufacturing.com

Nitrotel Manufacturing
Low Voltage Products & Fiber Optic

Main Part

S/N	Specification	Qty	Material	Surface Finish	Remark
1	Top Cover	1	SPCC t1.0	Powder coated	----
2	Bottom Plate	1	SPCC t1.0	Powder coated	----
3	Front door	1	5MM toughed glass door SPCC t1.0	----	Small lock
4	19" rails	2	SPCC t1.5	Powder coated	----
5	Side Panels	2	SPCC t1.0	Powder coated	----

Specification

Model N o.	RU	Width (mm)	Depth(D)(mm)	Height(H)(mm)	Static Loading Capacity (kg)
NTSOHO6U500	6	530	450	370	40
NTSOHO9U500	9	530	450	500	45
NTSOHO12U500	12	530	450	635	50

Details